

wysLink



model : bCam-1

Waterproof battery camera

price	name	Wi-Fi battery camera
describe	features	wireless connection, Ultra-low power consumption, Remote active awakening, Quick start
	use	Visitors can make a video call and make a short video recording so that the owner can find out the information
	Wake up the way	PIR human body detects and wakes up, mobile phone wakes up
	Alarm push	Push notification to phone within 1 second
operating system	Number of users online	Multiple users up to 4 are online simultaneously
	processor	A powerful, high-performance, programmable media HiSilicon processor with built-in ARM926 @max. 440MHz and high-speed video coprocessor

collect	CCD	1/4 inch 720p scan CMOS sensor
	Sensor performance	Support automatic white balance, automatic gain control, automatic backlighting compensation
	SNR	≥39dB
	LUX	0.8Lux/F1.4 (Color pattern) ,0.3Lux/F1.4 (Black and white pattern)
	Lens/visual Angle	1.7mm@F2.4/166°
	LED	Double filter automatic switching, six 850 - nm Φ 28 mil high power infrared lamp, night vision 10 meters
	IR control	IR opens night vision, Automatic detection of infrared and ICR ; IR shuts the night vision function off the infrared and the ICR is fixed in daily viewing mode
video	Compression standard	H.264 Main Profile/H.264 Baseline Profile/MJPEG/JPEG Baseline
	Video coding	More stream : 720P/24fps+VGA/30fps+QVGA/30fps+720P @1fsJPEG snap
	resolution	1080*720
audio	input	1 channel built-in - 48dB microphone
	output	Built-in speaker (8 Ω 1 w)
	interphone	Two - way voice - speak, bring back the echo cancellation
	Compression standard/ code rate	ADPCM/32kbps
network	Network protocol	TCP/IP,HTTP,TCP,UDP,SMTP,FTP,DHCP,DNS,DDNS,NTP,UPnP,RTSP, P2P
	wireless network	802.11b/g/n

network	Wireless network security	WPS Security encryption
	wireless connection	WIFI configuration via phone sound
video	Video mode	Mobile detection video, doorbell button trigger video, manual video
	storage	The TF card stores the maximum support for 32gb
other	power	Battery-powered two 18650 batteries, international; USB 5V power supply
	Power consumption	Standby current 120 uA working current 170MA
	work environment	Working temperature: - 20 ~ 50 °C, humidity is < 95%
	installation	Wall mounting
	material	ABS
	Water-proof Level	IP54 (rainproof)
	Product size	Length 96.5mm X Diameter 65.5mm
	product weight	2 pcs of 18650 3.7V batteries
	Packing size	100mm X 175mm X 77.5mm



TEL. 1-416-855-2781
www.wysLink.com