

model : wBel-1



wysLink

Wi-Fi Video Doorbell

description	features	Wi-Fi connection, Ultra-low power consumption, Remote active awakening, Quick start
	Functions	Visitor is able to make video voice calls and take short videos. Owner can talk with visitors no matter where he is
	Wake up	Doorbell button pushed; PIR body detected; Mobile phone calls bell
	Alarm push	Push notification to phone within 1 second
operating system	Number of users online	Multiple users up to 4 are online simultaneously
	processor	A powerful, high-performance, programmable media HiSilicon processor with built-in ARM926 @max. 440MHz and high-speed video coprocessor
collect	CCD	1/4 inch 720p scan CMOS sensor
	Sensor performance	Support automatic white balance, automatic gain control, automatic backlighting compensation
	SNR	≥39dB
	LUX	0.8Lux/F1.4 (Color pattern) ,0.3Lux/F1.4 (Black and white pattern)
	Lens/visual Angle	1.7mm@F2.4/166°
	LED	Double filter automatic switching, 6pcs of 850nm Φ 28 mil high power infrared lamps, night vision up to 10 meters
video	IR control	Automatically
	Compression standard	H.264 Main Profile/H.264 Baseline Profile/MJPEG/JPEG Baseline
	Video coding	More stream : 720P/24fps+VGA/30fps+QVGA/30fps+720P @1fsJPEG snap
audio	resolution	1080*720
	input	1 channel built-in - 48dB microphone
	output	Built-in speaker (8 Ω 1 w)
	interphone	Two - way voice talk, with function of Echo suppression and cancellation
network	Compression standard/code rate	ADPCM/32kbps
	Network protocol	TCP/IP,HTTP,TCP,UDP,SMTP,FTP,DHCP,DNS,DDNS,NTP,UPnP,RTSP, P2P
	wireless network	802.11b/g/n
	Wireless network security	WPS Security encryption
video	wireless connection	WIFI configuration via phone sound
	Video mode	Mobile detection video, doorbell button trigger video, manual video
	storage	The TF card stores the maximum support for 32gb
other	power	Supports battery power (1 section 6000MHA lithium battery assembly), USB 5V power supply, AC16~24V power supply
	Power consumption	Standby current 120 uA working current 170mA
	work environment	Working temperature: - 20 ~ 50 °C, humidity is < 95%
	installation	Door wall mounting
	material	ABS
	Water-proof Level	IP53 (rainproof)
	Product size	136mm x 70mm x32.5mm
	product weight	180g/No battery
Packing size	188mmx106mmx46mm	